

NPS	OD Inches	Designations	Wall Thickness (Inches)	Inside Diam (Inches)	Weight (lbs./ft.)
1/8	0.405	10/10S	0.049	0.307	0.1863
		Std./40/40S	0.068	0.269	0.2447
		XS/80/80S	0.095	0.215	0.3145
1/4	0.540	10/10S	0.065	0.410	0.3297
		Std./40/40S	0.088	0.364	0.4248
		XS/80/80S	0.119	0.302	0.5351
3/8	0.675	10/10S	0.065	0.545	0.4235
		Std./40/40S	0.091	0.493	0.5676
		XS/80/80S	0.126	0.423	0.7388
1/2	0.840	5/5S	0.065	0.710	0.5383
		10/10S	0.083	0.674	0.6710
		Std./40/40S	0.119	0.622	0.8510
		XS/80/80S	0.147	0.546	1.0880
		160	0.188	0.466	1.3090
		XX	0.294	0.252	1.7140
3/4	1.050	5/5S	0.065	0.920	0.6838
		10/10S	0.083	0.884	0.8572
		Std./40/40S	0.113	0.824	1.1310
		XS/80/80S	0.154	0.742	1.4740
		160	0.219	0.618	1.9440
		XX	0.308	0.434	2.4410
1	1.315	5/5S	0.065	1.185	0.8678
		10/10S	0.109	1.097	1.4040
		Std./40/40S	0.133	1.049	1.6790
		XS/80/80S	0.179	0.957	2.1720
		160	0.250	0.815	2.8440
		XX	0.358	0.599	3.6590
1 1/4	1.660	5/5S	0.065	1.530	1.1070
		10/10S	0.109	1.442	1.8060
		Std./40/40S	0.140	1.380	2.2730
		XS/80/80S	0.191	1.278	2.9970
		160	0.250	1.160	3.7650
		XX	0.382	0.896	5.2140
1 1/2	1.900	5/5S	0.065	1.770	1.2740
		10/10S	0.109	1.682	2.0850
		Std./40/40S	0.145	1.610	2.7180
		XS/80/80S	0.200	1.500	3.6310
		160	0.281	1.338	4.8590
		XX	0.400	1.100	6.4080
2	2.375	5/5S	0.065	2.245	1.6040
		10/10S	0.109	2.157	2.6380
		Std./40/40S	0.154	2.067	3.6530
		XS/80/80S	0.218	1.939	5.0220
		160	0.344	1.689	7.4620
		XX	0.436	1.503	9.0290
2 1/2	2.875	5/5S	0.083	2.709	2.4750
		10/10S	0.120	2.635	3.5310
		Std./40/40S	0.203	2.469	5.7930
		XS/80/80S	0.276	2.323	7.6610
		160	0.375	2.125	10.0100
		XX	0.552	1.771	13.6900
3	3.500	5/5S	0.083	3.334	3.0290
		10/10S	0.120	3.260	4.3320
		Std./40/40S	0.216	3.068	7.5760
		XS/80/80S	0.300	2.900	10.2500
		160	0.438	2.624	14.3200
		XX	0.600	2.300	18.5800
3 1/2	4.000	5/5S	0.083	3.834	3.4720
		10/10S	0.120	3.760	4.9730
		Std./40/40S	0.226	3.548	9.1090
		XS/80/80S	0.318	3.364	12.5000
		160	0.463	3.063	17.2800
		XX	0.636	2.728	22.8500
4	4.500	5/5S	0.083	4.334	3.9150
		10/10S	0.120	4.260	5.6130
		Std./40/40S	0.237	4.026	10.7900
		XS/80/80S	0.337	3.826	14.9800
		120	0.438	3.624	19.0000
		160	0.531	3.438	22.5100
XX	0.674	3.152	27.5400		
4 1/2	5.000	Std./40/40S	0.247	4.506	12.5300
		XS/80/80S	0.355	4.290	17.6100
		XX	0.710	3.580	32.4300
5	5.563	5/5S	0.109	5.345	6.3490
		10/10S	0.134	5.295	7.7700
		Std./40/40S	0.258	5.047	14.6200
		XS/80/80S	0.375	4.813	20.7800
		120	0.500	4.563	27.0400
		160	0.625	4.313	32.9600
XX	0.750	4.063	38.5500		

NPS	OD Inches	Designations	Wall Thickness (Inches)	Inside Diam (Inches)	Weight (lbs./ft.)
6	6.625	5/5S	0.109	6.407	7.585
		10/10S	0.134	6.357	9.289
		Std./40/40S	0.280	6.065	18.970
		XS/80/80S	0.432	5.761	28.570
		120	0.562	5.491	36.390
7	7.625	160	0.719	5.189	45.350
		XX	0.864	4.897	53.160
		Std./40/40S	0.301	7.023	23.570
8	8.625	XS/80/80S	0.500	6.625	38.050
		XX	0.875	5.875	63.080
		5S	0.109	8.407	9.914
9	9.625	10/10S	0.148	8.329	13.400
		20	0.250	8.125	22.360
		30	0.277	8.071	24.700
		Std./40/40S	0.322	7.981	28.550
		60	0.406	7.813	35.640
		XS/80/80S	0.500	7.625	43.390
		100	0.594	7.439	50.950
		120	0.719	7.189	60.710
		140	0.812	7.001	67.760
		160	0.875	6.875	72.420
10	10.750	160	0.906	6.813	74.690
		Std./40/40S	0.342	8.941	33.900
		XS/80/80S	0.500	8.625	48.720
		XX	0.875	7.875	81.770
		5S	0.134	10.482	15.190
		10S	0.165	10.420	18.700
		20	0.250	10.250	28.040
		30	0.307	10.136	34.240
		Std./40/40S	0.365	10.020	40.480
		XS/60/80S	0.500	9.750	54.740
11	11.750	80	0.594	9.564	64.430
		100	0.719	9.314	77.030
		120	0.844	9.064	89.290
		140	1.000	8.750	104.130
		160	1.125	8.500	115.640
		Std./40/40S	0.375	11.000	45.550
		XS/80/80S	0.500	10.750	60.070
		XX	0.875	10.000	101.630
		5S	0.165	12.420	22.180
		10S	0.180	12.390	24.200
12	12.750	20	0.250	12.250	33.380
		30	0.330	12.090	43.770
		Std./40S	0.375	12.000	49.560
		40	0.406	11.938	53.530
		XS/80S	0.500	11.750	65.420
		10S	0.188	13.624	27.730
14	14.000	10	0.250	13.500	36.710
		20	0.312	13.376	45.610
		Std./30/40S	0.375	13.250	54.570
		40	0.438	13.124	63.440
		XS/80S	0.500	13.000	72.090
		60	0.594	12.814	85.050
		80	0.750	12.150	106.130
		100	0.938	12.126	130.850
		120	1.094	11.814	150.900
		140	1.250	11.500	170.210
16	16.000	160	1.406	11.188	189.100
		10S	0.188	15.624	31.750
		10	0.250	15.500	42.050
		20	0.312	15.376	52.270
		Std./30/40S	0.375	15.250	62.580
		XS/40/80S	0.500	15.000	82.770
		60	0.656	14.688	107.500
		80	0.844	14.314	136.610
		100	1.031	13.938	164.820
		120	1.219	13.564	192.430
16	16.000	140	1.438	13.124	223.640
		160	1.594	12.814	245.250
		10	0.312	33.376	112.250
		Std.	0.375	33.250	134.670
		20	0.500	33.000	178.890
		30	0.625	32.750	222.780
32	32.000	40	0.688	32.624	244.770
		10	0.312	35.375	118.920
		Std./40S	0.375	35.250	142.680
		20	0.500	35.000	189.570
		30	0.625	41.250	166.710
		40	0.750	41.000	221.610
42	42.000	30	0.625	40.750	276.180
		40	0.750	40.500	330.410
		Std./40S	0.375	47.250	190.740
		XS/80S	0.500	47.000	253.650
		30	0.625	47.000	253.650
		40	0.750	47.000	253.650

NPS	OD Inches	Designations	Wall Thickness (Inches)	Inside Diam (Inches)	Weight (lbs./ft.)		
18	18.000	10S	0.188	17.624	35.760		
		10	0.250	17.500	47.390		
		20	0.312	17.376	58.940		
		Std./40S	0.375	17.250	70.590		
		30	0.438	17.124	82.150		
		XS/80S	0.500	17.000	93.450		
		40	0.562	16.876	104.670		
		60	0.750	16.500	138.170		
		80	0.938	16.126	170.920		
		100	1.156	15.688	207.960		
		120	1.375	15.250	244.140		
		140	1.562	14.876	274.220		
		160	1.781	14.438	308.500		
		20	20.000	10	0.250	19.500	52.730
				20	0.375	19.250	78.600
				30	0.500	19.000	104.130
40	0.625			18.814	123.110		
60	0.812			18.376	166.400		
80	1.031			17.938	208.870		
22	22.000	100	1.281	17.438	256.100		
		120	1.500	17.000	296.370		
		140	1.750	16.500	341.090		
		160	1.969	16.064	379.170		
		10/10S	0.250	21.500	58.070		
		Std./20/40S	0.375	21.250	86.610		
		XS/30/80S	0.500	21.000	114.810		
		60	0.875	20.250	197.410		
		80	1.125	19.750	250.810		
		100	1.375	19.250	302.880		
24	24.000	120	1.625	18.750	353.610		
		140	1.875	18.250	403.000		
		160	2.125	17.750	451.060		
		10/10S	0.250	23.500	63.410		
		Std./20/40S	0.375	23.250	94.620		
		XS/80S	0.500	23.000	125.490		
		30	0.562	22.876	140.680		
		40	0.688	22.626	171.290		
		60	0.969	22.064	238.350		
		80	1.219	21.564	296.580		
26	26.000	100	1.531	20.938	367.390		
		120	1.812	20.376	429.390		
		140	2.062	19.876	483.100		
		160	2.344	19.314	542.130		
		10	0.312	25.376	85.600		
		Std./40S	0.375	25.250	102.630		
28	28.000	XS/80S	0.500	25.000	136.170		
		10	0.312	27.376	92.260		
		20/80S	0.375	27.250	110.640		
30	30.000	30	0.625	26.750	182.730		
		10	0.312				

PIPE, VALVES, FITTINGS AND SPECIALTY APPLICATION PRODUCTS



Simply Our Way of Life

The demands of our industry are second nature to us. Complicated product specifications are our daily fodder. We breathe the urgency of tight deadlines.

With over 25 years experience, we possess a special expertise for challenging installations. Because no two projects are ever alike, we approach each assignment with innovation and commitment to the end result. For us, knowing what works and what doesn't goes beyond basic knowledge; it runs in our blood!

Your Success is our Livelihood

Our clients have come to regard us as extensions of their own operations; partners who only see mutual success. From pre-order technical support through final product delivery, we honor the trust our customers place in us with each and every order. Because – ultimately – we know that your success is what keeps us going...



We supply stainless steel pipe, valves and fittings for limitless applications and specialize in exotic materials such as Duplex, Super Duplex, 6Moly, Inconel and Titanium.

Our extensive global sources of manufacturers and distributors enable us to provide competitive prices and short lead times for quality products.

Our expert staff – from sales to expediting - is supported by well-developed, custom logistic solutions in order to deliver superior follow-up and unparalleled service.

Compare our prices and experience our product knowledge!

Send your next inquiry to sales@pmfirst.com

PROJECTS

Shell International Exploration & Production Inc

Ursa Princess Waterflood Project
Mississippi Canyon Block 810A
Gulf of Mexico

Petrobras

FPSO P52
FPSO P53
FPSO P54

Chevron North American Exploration and Production Co.

Tahiti Project
Green Canyon Block 640
Gulf of Mexico Blind Faith Project

ExxonMobil

Kizomba A & B
Kizomba C Development
Mondo Field, Deepwater Block 15
Offshore Angola
Heater B101 Rehab
Heater B170 Rehab
Heater SOP-050020
Heater SOP-04-444
Heater JPF3033/TA_ID F3053
Singapore Transplus
Sable Island -Tier II Project
Hibernia

Statoil-Norge

Ormen Lange
Kristin
Sleipner A Modification Project
Gulflaks A

Norsk Hydro

Porsgrunn

Vetco Aibel

PetroCanada

Terra Nova

Husky Energy

White Rose

ESSO Australia

EAPL Project

Shell Todd Oil Services

Pohokura Project

BP

Atlantis

Woodside Australian Energy

British Gas

Armada Project

South Hook LNG Terminal Co Ltd

Exxon Neftegas Ltd

Sakhalin Export Terminal

Aker Kvaerner

Cameron LNG Project

Kvaerner Oil & Gas

Asgard B Project



PRODUCTS

TITANIUM

Grades 1, 2, 5, 7, 9 & 12

Seamless Tubing
Seamless Pipe
Round Bar
Plate/Sheet
Seamless & Welded Butt-weld Fittings
Specialty Forgings

6 MOLY

UNS S31254, N08926 & N08925

Plate/Sheet
Seamless & Welded Tube
Seamless & Welded Pipe
Round Bar
Flanges
Seamless & Welded Butt-weld Fittings
Specialty Forgings

DUPLEX

UNS S31803 & S32205

Plate/Sheet
Seamless & Welded Tube
Seamless & Welded Pipe
Round Bar
Flanges
Seamless & Welded Butt-weld Fittings
Specialty Forgings

SUPER DUPLEX

UNS S32750 & S32760

Plate/Sheet
Seamless & Welded Tube
Seamless & Welded Pipe
Round Bar
Flanges
Seamless & Welded Butt-weld Fittings
Specialty Forgings

VALVE TYPES

Ball Valves

Check Valves
Gate Valves
Globe Valves
Butterfly Valves
Double Block & Bleed Valves
Instrumentation Valves
and more...

VALVE MATERIALS

Titanium Grades 2, 7 & 12

Duplex UNS S31803 & S32205,
Super Duplex UNS S32750 & S32760,
6 Moly UNS S31254